

# ROQ DRY

The cure units developed by ROQ work in sync with any ROQ automatic screen printing machines. They present different technological levels and settings so that they can respond to any work.

ROQ Dry Moby	20250 4XL
drying area (mm / inch)	1020 x 380 / 40" x 15" + travel*
power supply (VAC)	(1) (2)
max. consumption (kVA)	20.25
power/area (W/cm)	5.23
plug (min. recommended)	63A (3x230V) 32A (3x400V)
total length (mm / feet)	1685 / 5.53'
total height (mm / feet)	1400 / 4.6'
total width (mm / feet)	1125 / 3.7'

\* travel: 1100mm / 43"  
(1) 230 VAC | (2) 2x230 VAC



## ROQ Dry Moby

- Digital control panel that regulates time, temperature and drying area
- Heat transmission by convection and radiation
- Suitable for larger drying areas

ROQ Dry Run	3000 S	9000 M	14400 XL	18000 XL+	20400 2XL	25500 3XL	25500 4XL
drying area (mm / inch)	200x200 / 7.9"x7.9"	400x500 / 16"x20"	500x700 / 20"x28"	600x800 / 24"x31"	700x1000 / 28"x39"	800x1100 / 31"x43"	900x1100 / 35"x43"
power supply (VAC)	(1) (2) (3) (4)				(3) (4)		
max. consumption (kVA)	3	9	14.4	18	20.4	25.5	25.5
power/area (W/cm)	7.5	4.50	4.11	3.75	2.91	2.90	2.58
lamps	6 x 500	9 x 1000W	12 x 1200W	15 x 1200W	24 x 850W	30 x 850W	30 x 850W
plug (min. recommended)	(1) (2) (3) (4) - 32A	(1) (2) - 63A (3) (4) - 32A	(1) (2) (3) - 63A (4) - 32A	(1) (2) - 125A (3) - 63A (4) - 32A	(3) - 63A (4) - 32A	(3) - 125A (4) - 63A	
total length (mm / feet)	815 / 2.67'	920 / 3'	1140 / 3.74'	1240 / 4.06'	1520 / 4.97'	1630 / 5.35'	1630 / 5.35'
total height (mm / feet)	1220 / 4'						
total width (mm / feet)	625 / 2.05'	625 / 2.05'	625 / 2.05'	715 / 2.35'	835 / 2.74'	935 / 3.07'	1020 / 3.35'

(1) 230 VAC | (2) 2x230 VAC | (3) 3x230 VAC | (4) 4x230 VAC

ROQ Dry Evolution	12100 L	14400 XL	18000 XL+	20400 2XL	25500 3XL	25500 4XL
drying area (mm / inch)	450x550 / 17"x21"	500x700 / 20"x28"	600x800 / 24"x31"	700x1000 / 28"x39"	800x1100 / 31"x43"	900x1100 / 35"x43"
power supply (VAC)	(1) (2) (3) (4)			(3) (4)		
max. consumption (kVA)	12.1	14.4	18	20.4	25.5	25.5
power/area (W/cm)	4.3	4.11	3.7	2.91	2.89	2.58
lamps	11 x 1100W	12 x 1200W	15 x 1200W	24 x 850W	30 x 850W	30 x 850W
plug (min. recommended)	(1) (2) - 63A (3) (4) - 32A		(1) (2) - 125A (3) - 63A (4) - 32A	(3) - 63A (4) - 32A	(3) - 125A (4) - 63A	
total length (mm / feet)	1070 / 3.51'	1140 / 3.74'	1180 / 3.87'	1530 / 5.02'	1590 / 5.22'	1590 / 5.22'
total height (mm / feet)	1280 / 4.20'					
total width (mm / feet)	625 / 2.05'	625 / 2.05'	715 / 2.35'	835 / 2.74'	935 / 3.07'	1020 / 3.35'

(1) 230 VAC | (2) 2x230 VAC | (3) 3x230 VAC | (4) 4x230 VAC



## ROQ Dry Run

- Construction optimized for performance
- Heat transmission by convection and radiation



## ROQ Dry Evolution

- Digital control panel that regulates time, temperature and drying area
- Heat transmission by convection and radiation
- The curing unit rotates 90° making this model extremely versatile

Optional: Temperature probe (Smart), Turbo